

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Workstation CELSIUS W550

Affordable, Expandable, Scalable

Has your desktop reached the limit in terms of performance, scalability and expandability? Then the FUJITSU CELSIUS W550 desktop workstation is your ideal choice, especially for video editing, MCAD/ electrical CAD or Architecture, Engineering and Construction applications. Enjoy best-in-class low noise emissions of only 18 dB(A) for a quiet and efficient working environment.



Abundant performance at an affordable price

Enjoy impressive professional graphics and storage capacity at an affordable price

- Choose between the energy-efficient Intel® Core™ processors or the powerful Intel® Xeon® E3-1200 v5 processor family
- Support of Windows 10 Pro
- Broad choice of graphics cards, starting from the cost-effective integrated Intel graphic card, up to professional 2D and even high-end 3D graphics cards from AMD and NVIDIA
- Boost your storage performance with super-fast PCIe SSDs to provide a quick loading of core applications and reliable high-endurance and business critical drives designed for long-term operation

Expandability and scalability

For better graphical and storage performance, choose the power model of the CELSIUS W550

- 500W power supply for maximum graphic card configurability: up to the high-end 3D AMD FirePro™ W7000 series as well as the NVIDIA® Quadro® M4000 graphics cards
- The system will accommodate a total of five storage drives which can add up to an impressive capacity of 27.5 TB

Whisper quiet design Made in Germany

Fujitsu's desktop workstations are designed, engineered and manufactured in the heart of Europe

- Optimized thermal management and cooling solutions
- NVIDIA® NVS™ 315 fanless graphic card
- Enjoy a silent workplace environment thanks to a low noise emission of only 18 dB(A)

Multi-monitor experience

Enjoy maximum viewing capabilities and increase your productivity

- Support 4 monitors when choosing AMD Eyefinity™ or NVIDIA® Mosaic™ technologies
- Up to 8 monitors when selecting Nvidia's professional 2D graphics



RADEON PRO WX



Components

Processor	<p>Intel® Xeon® processor E3-1280v5 (4 Cores / 8 Threads, 3.70 GHz, up to 4.0 GHz, 8 MB) *, **</p> <p>Intel® Xeon® processor E3-1275v5 (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics P530) *, **</p> <p>Intel® Xeon® processor E3-1270v5 (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB) *, **</p> <p>Intel® Xeon® processor E3-1245v5 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics P530) *, **</p> <p>Intel® Xeon® processor E3-1240v5 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB) *, **</p> <p>Intel® Xeon® processor E3-1230v5 (4 Cores / 8 Threads, 3.40 GHz, up to 3.8 GHz, 8 MB) *, **</p> <p>Intel® Xeon® processor E3-1225v5 (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 8 MB, Intel® HD Graphics P530) *, **</p> <p>Intel® Xeon® processor E3-1220v5 (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 8 MB) *, **</p> <p>Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, **</p> <p>Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, **</p> <p>Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, **</p> <p>Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) **</p> <p>Intel® vPro™ with all Intel® Xeon® processors No Intel® vPro™ technology with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)</p>	
Operating systems		
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Operating system compatible	Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Windows 7 Professional 64-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Linux	Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Windows 7 Professional 64-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Linux
Operating system notes	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server For some configurations third party drivers are currently not available or configuration restrictions may apply. Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com .	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server For some configurations third party drivers are currently not available or configuration restrictions may apply.
Memory modules	<p>4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM</p> <p>8 GB (1 module(s) 8 GB) DDR4, unbuffered, ECC, 2,133 MHz, UDIMM</p> <p>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM</p> <p>16 GB (1 module(s) 16 GB) DDR4, unbuffered, ECC, 2,133 MHz, UDIMM</p> <p>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM</p>	

Graphics	High-end 3D: AMD FirePro™ W7100, 8 GB, PCIe x16, 4 x DisplayPort
	High-end 3D: NVIDIA® Quadro® P4000, 8 GB, PCIe x16, 4 x DisplayPort
	Midrange 3D: NVIDIA® Quadro® P2000, 5 GB, PCIe x16, 4 x DisplayPort
	Midrange 3D: AMD Radeon™ Pro WX 5100, 8 GB, 320 stream processors, PCIe x16, 4 x DisplayPort
	Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4x miniDP
	Entry 3D: AMD Radeon™ Pro WX 3100, 4 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP
	Entry 3D: NVIDIA® Quadro® P600, 2 GB, PCIe x16, 4x miniDP
	Professional 2D: NVIDIA® NVS™ 315 fanless, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I)
	Entry 3D: AMD Radeon™ Pro WX 2100, 2 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP
	Entry 3D: NVIDIA® Quadro® P620, 2 GB, PCIe x16, 4x miniDP
	Entry 3D: NVIDIA® Quadro® P400, 2 GB, PCIe x16, 3x miniDP
	Professional 2D: NVIDIA® NVS™ 510, 2 GB, 16 cores, PCIe 2.0 x16, 4x miniDP, 4x miniDP/DP Adapter
	Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I)
	Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP
	Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP
	Others: DP to DVI-D (single link) Adapter Cable
	Others: VGA Extension Card
Notes	NVIDIA® Quadro® M4000 and ATI FirePro™ W7100 require CELSIUS W550power.
	NVIDIA® Quadro® M4000 and P4000 require CELSIUS W550power.
Hard disk drives (internal)	SSD SATA III, 480 GB High Endurance, 3DWP, 2.5-inch
	SSD SATA III, 240 GB High Endurance, 3DWP, 2.5-inch
	SSD PCIe, 1024 GB M.2 NVMe Highend module
	SSD PCIe, 512 GB M.2 NVMe Highend module
	SSD PCIe, 256 GB M.2 NVMe Highend module
	SSD PCIe, 1x1024 GB M.2 NVMe Highend card
	SSD PCIe, 1x 512 GB M.2 NVMe Highend card
	SSD PCIe, 1x 256 GB M.2 NVMe Highend card
	SSD SATA III, 1024 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
	HDD SATA III, 7,200 rpm, 6,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1000 GB, 2.5-inch, enhanced availability
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	24/7 ready (business critical HDDs required)
	Up to 20 GB of HDD space is reserved for system recovery
	SSHD (Solid State Hard Disk, Hybrid drive)
	SED (Self-Encrypting Drive) SSD (Solid State Disk)

Drives (optional)	BD Triple Writer SATA ultra slim (tray)
	DVD-ROM
	DVD Super Multi
	DVD Super Multi ultra slim (tray)
	MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)
	WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)
	Parallel Interface
	Gigabit Ethernet PCIe x1
	eSATA Interface
	Dual serial card PCIe x1
Base unit	CELSIUS W550
	CELSIUS W550power
Mainboard	
Mainboard type	D3417
Formfactor	µATX
Chipset	Intel® C236
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	4 DIMM (DDR4) ECC/non-ECC
Memory frequency	2,133 MHz
Memory notes	Dual channel support For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS version	AMI Aptio V
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	6
thereof SATA III	6
thereof eSATA	2 (optional)
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
Internal speakers	1
USB 2.0 total	6

Interfaces

USB 3.1 Gen1 (USB 3.0) total	7
USB front	2x USB 2.0; 2x USB 3.0
USB rear	2x USB 2.0; 4x USB 3.0
USB internal	2x USB 2.0 + 1x USB 3.0
VGA	optional: via adapter card
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO Space Explorer USB
--------------------------	--

Drive bays

Drive bays total	7	9
2.5-inch internal bays	1	1
3.5-inch internal bays	2	4
3.5-inch external bays	2	2
5.25-inch external bays	2	2
Drive bay notes	Up to 1x 2.5-inch HDDs and up to 2x 2.5/3.5-inch HDDs	Up to 1x 2.5-inch HDDs and up to 4x 2.5/3.5-inch HDDs
M.2-2280	1 x on mainboard (for PCIe SSD modules)	1 x on mainboard (for PCIe SSD modules)

Slots

PCI-Express 3.0 x1	2 x (340 mm / 170 mm / 13.39 inch / 6.69 inch) Full height
PCI-Express 3.0 x4 (mech. x16)	1 x (170 mm / 6.69 inch) Full height
PCI-Express 3.0 x16	1 x (340 mm / 13.39 inch) Full height

Graphics on board

Graphics brand name	Intel® HD Graphics P530, Intel® HD Graphics 530
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel

Graphics on board

TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 84% / 88% / 92% / 90%	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 84% / 91% / 93% / 91%
Rated voltage range	100 V - 240 V	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz	47 Hz - 63 Hz
Max. output of single power supply	300 W	500 W
Power factor correction/active power	active	active
Power supply output		1 graphics power rail (6pin connector / 17A@12V)

Noise for standard configuration (HDD, ODD)

Noise emission	According to ISO9296	According to ISO9296
Related Processors for noise	Intel® Xeon® E3-1275v5	Intel® Xeon® E3-1275v5
Standard noise emission	4x8 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74	4x8 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lw _{ad} (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A)) (depending on configuration)	A-weighted sound power level Lw _{ad} (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A)) (depending on configuration)
Standard noise operation mode: CPU 50% load	3.5 B / 20 dB(A) Bystander position	3.5 B / 21 dB(A) Bystander position
Standard noise operation mode: CPU 90% load	3.5 B / 21 dB(A) Bystander position	3.5 B / 22 dB(A) Bystander position
Standard noise operation mode: HDD load	3.5 B / 21 dB(A) Bystander position	3.5 B / 21 dB(A) Bystander position
Standard noise operation mode: Idle mode	3.3 B / 19 dB(A) Bystander position	3.4 B / 21 dB(A) Bystander position
Standard noise operation mode: ODD load	4.3 B / 29 dB(A) Bystander position	4.4 B / 29 dB(A) Bystander position
Standard noise operation mode: Office applications 2.0	3.3 B / 19 dB(A) Bystander position	3.4 B / 21 dB(A) Bystander position

Noise for standard configuration (HDD, ODD)

Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level Lw _{ad} (in B); 1B = 10dB	A-weighted sound power level Lw _{ad} (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.6 B = 36 dB (A)	3.9 B = 44 dB (A)
Blue angel noise operation mode: Idle mode	3.6 B = 36 dB (A)	3.9 B = 44 dB (A)
Blue angel noise operation mode: ODD load	4.4 B = 44 dB (A)	4.4 B = 44 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 419 x 395 mm 6.89 x 16.5 x 15.56 inch	
Operating position	Vertical	
Weight	approx. 11 kg	approx. 14 kg
Weight (lbs)	approx. 24.25 lbs	approx. 30.86 lbs
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	10 - 35 °C (50 - 95 °F)	
Operating relative humidity	5 - 85 % (relative humidity)	

Compliance

Product	CELSIUS W550	CELSIUS W550power
Model	M15W	
Germany	GS (planned)	
Europe	CE	
USA/Canada	FCC Class B cCSAus	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions)	
China	CCC (planned) China RoHS	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	

Additional Software

Additional software (preinstalled)	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)	

Security

Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
--------------------------	--	--

Security		
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) Easy Restore (optional)	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) Easy Restore (optional)
Manageability		
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 11.0 (depending on processor)	
Manageability software	DeskView Client DeskView Instant BIOS Management	
DeskView components	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)	
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)	
Manageability link	http://www.fujitsu.com/fts/manageability	
Miscellaneous		
	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime 24/7 (limited configurations)	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime 24/7 (limited configurations)
Packaging information		
Packaging dimension (mm)	516 x 278 x 562 mm	516 x 278 x 562 mm
Packaging dimension (inch)	20.31 x 10.94 x 22.13 inch	20.31 x 10.94 x 22.13 inch
Max. quantity / pallet	24	24
Material - Weight (g) Carton	1280 g	1280 g
Material - Weight (lbs) Carton	2.82 lbs	2.82 lbs
Material - Weight (g) EPS / PS	190 g	190 g
Material - Weight (lbs) EPS / PS	0.42 lbs	0.42 lbs
Material - Weight (g) PE	60 g	60 g
Material - Weight (lbs) PE	0.13 lbs	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Related Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life 5 years
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display P27-8 TS Pro

If you're a pixel, color and performance-hungry professional using demanding applications, the FUJITSU P27-8 TS Pro Display is the perfect choice. The display provides outstanding picture performance thanks to cutting-edge panel technology and 3.7 Mio pixels. It also boasts unique and innovative features such as our patent-applied Presence Sensor technology and USB support during standby.

Order Code:
S26361-K1594-V160

Display B34-9 UE

The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ Click manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1642-V140

SpaceMouse™ Pro

Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Wireless Keyboard Set LX901

The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption.

S26381-K565-L4** (**:
Country specific variation)

More information

Fujitsu products, solutions & services

In addition to the FUJITSU Workstation CELSIUS W550, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS W550, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2019-01-18 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions